


# Easy Universal Sway Brace – CSBEZU0100EG



- Use for both lateral and longitudinal sway brace applications
- Unique slotted holes provide for easy slip-on installation eliminating loose hardware
- Snap-off bolt head helps enable easy installation and inspection of seismic sway braces
- Works with 1" through 2" brace pipes and 1/4" angle iron braces to reduce inventory
- Meets NFPA®-13 requirements for seismic sway bracing



Part Number	CSBEZU0100EG
Material	Steel
Finish	Electrogalvanized
Pipe Size	1"
A	6 7/8"
B	1"
Brace Pipe Size	1" – 2"
Certifications	cULus FM OSHPD
Standard Packaging Quantity	10 pc
UPC	78285663422
EAN-13	8711893057751

UL Loads (Listed for Restraints)			
Part Number	Dyna-Flow® Service Pipe	Sch 10 Service Pipe	Sch 40 Service Pipe
CSBEZU0100EG	N/A	655 lb	655 lb
CSBEZU0125EG	655 lb	655 lb	655 lb
CSBEZU0150EG	655 lb	655 lb	655 lb



UL Loads (Listed for Sway Braces)								
Part Number	Lateral				Longitudinal			
	Dyna-Flow® Service Pipe	EZ FLOW™ Service Pipe	Sch 10 Service Pipe	Sch 40 Service Pipe	Dyna-Flow® Service Pipe	Mega-Flow Service Pipe	Sch 10 Service Pipe	Sch 40 Service Pipe
CSBEZU0200EG	3,000 lb	N/A	3,000 lb	3,000 lb	N/A	N/A	N/A	N/A
CSBEZU0250EG	3,000 lb	N/A	3,000 lb	3,000 lb	1,265 lb	N/A	1,265 lb	1,265 lb
CSBEZU0300EG	3,000 lb	N/A	3,000 lb	3,000 lb	1,265 lb	N/A	1,265 lb	1,265 lb
CSBEZU0400EG	3,000 lb	3,000 lb	3,000 lb	3,000 lb	1,265 lb	N/A	1,265 lb	1,265 lb
CSBEZU0500EG	N/A	3,000 lb	3,000 lb	3,000 lb	N/A	1,600 lb	1,600 lb	1,600 lb
CSBEZU0600EG	N/A	3,000 lb	3,000 lb	3,000 lb	N/A	1,600 lb	1,600 lb	1,600 lb

FM Loads (Lightwall, Sch 10 and Sch 40 Service Pipes)								
Part Number	Horizontal Capacity per Installation Angle from Vertical							
	Lateral				Longitudinal			
	30° - 44°	45° - 59°	60° - 74°	75° - 90°	30° - 44°	45° - 59°	60° - 74°	75° - 90°
CSBEZU0100EG	860 lb	1,220 lb	1,500 lb	1,670 lb	390 lb	550 lb	670 lb	750 lb
CSBEZU0125EG	860 lb	1,220 lb	1,500 lb	1,670 lb	390 lb	550 lb	670 lb	750 lb
CSBEZU0150EG	860 lb	1,220 lb	1,500 lb	1,670 lb	390 lb	550 lb	670 lb	750 lb
CSBEZU0200EG	1,530 lb	2,160 lb	2,650 lb	2,960 lb	520 lb	690 lb	830 lb	930 lb
CSBEZU0250EG	1,530 lb	2,160 lb	2,650 lb	2,960 lb	520 lb	690 lb	830 lb	930 lb
CSBEZU0300EG	1,530 lb	2,160 lb	2,650 lb	2,960 lb	520 lb	690 lb	830 lb	930 lb
CSBEZU0400EG	1,570 lb	2,220 lb	2,720 lb	3,030 lb	630 lb	900 lb	1,100 lb	1,230 lb
CSBEZU0500EG	1,570 lb	2,220 lb	2,720 lb	3,030 lb	630 lb	900 lb	1,100 lb	1,230 lb
CSBEZU0600EG	1,980 lb	2,810 lb	3,440 lb	3,840 lb	730 lb	1,000 lb	1,230 lb	1,370 lb

Dyna-Flow is a registered trademark of Allied Tube & Conduit Corporation. FM is a registered certification mark of FM Approvals LLC, LTD. NFPA is a registered trademark of National Fire Protection Association, Inc. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

**WARNING**

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 Pentair All rights reserved  
Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.  
All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

